# IFD75TH653/3





## 75" Android Based Interactive Flat Panel Displays

## **Key Features**



#### **Palm Erase**

Automatic palm erasing function allows teachers and students to simplify the white board experience with smooth writing and erasing.



#### Ease of use with Android

Android gives teachers one touch access for lessons and collaboration tools including whiteboard, web browser, apps library, and native wireless screen sharing.





#### **Wireless Presentation**

Teachers, students or any user can share their screen efficiently and conveniently in the classroom or meeting room via EShare application. This application can connect any operating system and show up to 4 different screen at the same time.

#### **Different Sizes for various classrooms**

Available in a variety of large screen sizes, the IFD range gives customers the options to choose exactly what they need for their room size.



#### **Crestron Connected**

Crestron Connected certification complements VESTELs presence with inside the corporate, retail, government, better training and hospitality markets, all of which use expert AV controls. As those sectors hold to evolve with growing necessities for simple-to-use merchandise, seamless integration, dependable answers and community connectivity.

## IFD75TH653/3



#### DISPLAY

Screen Size Panel Technology Backlight Type Brightness (typical) Native Resolution Contrast Ratio (typical) Dynamic Constrast Ratio Panel Life Time (Min.) Response Time (typical) Active Area (H x V) Pixel Pitch (H x V) PPI (pixel per inch) Viewing Angle Color Value Screen Treatment Haze Level Refresh Rate Front Type Orientation Operation Hours Area of Usage

75" IPS Direct-Type LED 400 cd/m<sup>2</sup> UHD: 3840 x 2160 - HDR10 1200:1 40000:1 30.000 Hrs 8 ms 1650 x 928 mm 0.429 x 0.429 mm 59 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 1.07 B (10-bit) 2H 8% 60 Hz Touch Bezel Horizontal 16/7 Indoor

#### REAR I/OS

RGB Input VGA(DE-15F) RGB Output N/A 3xHDMI2.0 (HDCP2.2), 2xUSB2.0, USB2.0(Internal), 1xMicroSD Video Input HDMI2.0 Video Output Audio Input Line In L/R Headphone, Optic SPDIF Audio Output RS232(DE-9F), 2\*Ethernet(RJ45), Service(RJ12) External Control External Sensor RJ12

## MECHANICAL

Product Dimensions (WxDxH) Package Dimensions (WxDxH) Product Weight Package Weight Vesa Mounting Bezel Width 1731 x 119 x 1008 mm 1948 x 310 x 1248 mm 58.3 kg 72.4 kg 600 x 400 mm - M6 B:38 | T:38 | L/R:38 mm

#### POWER

Power Supply

FEATURES

Main Features	USB-Autoplay, Auto-switch on Failover, Control Button Lock, HDMI Wake-Up
Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying handles, Detachable logo positioning, Cable Holders
Optional Features	OPS Compliance
Speaker	2 x 12 W

110 VAC - 240 VAC - 50/60 Hz

#### CERTIFICATION

Safety	YES
EMC	YES
CE	YES

### BUILT-IN SYSTEM

Mainboard Model

17MB135VS

### TOUCH INTERACTIVITY

Type of Touch Technology Continuous Touch Points Sensitivity Connectivity Compatibility Orientation Calibration Accuracy Reporting Rate Glass Type Frame Rate Communication Power Supply Mode Supply Voltage Average Current Response Time Touch Accuracy Touch Durability HID Compatibility Object Sizes for Touch

Infrared (IR) Technology 10 Points Any touch with finger, gloved hand or pointer HID. TUIO. Flash HID, TUIO, Flash Windows<sup>®</sup>7,Windows<sup>®</sup>8, Windows<sup>®</sup> 10, Vista, XP, Mac<sup>®</sup> OS, Linux, Android Landscape support No need 90% < up to 450 fps Anti Glared (AG), Tempered 4mm up to 450 fps USB2.0 USB DC 5V +/- 5% < 400 mA < 10 ms +/-2mm (over 90% area) Unlimited YES USB 5 mm

### ENVIRONMENTAL CONDITIONS

Operating Temperature Operating Humidity 0-40°C 10-90%

## POWER CONSUMPTION

Active StandBy

≤ 0.5W

#### ACCESSORY

Standard

QSG, IB, Power Cord, Remote Control Unit, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable

